



Storage Systems

BATTERY INVERTER PBI 50K / 90K



- **ON-Grid Variant** – 50kVA and 90kVA
- **ON/OFF-Grid Variant** – 90kVA ON-Grid / 75kVA Backup without additional transformer*
 - **120% Backup overload capability**
 - **Phase unbalance up to 20kVA (without transformer)**
 - **Diode load (up to 1kW)**

*Only in combination with the Pramac Smart Transfer Switch (PSTS)




- **Commercial and Industrial Buildings** – Peak shaving, Self-consumption, Time of Use, Energy Trading, Multi- Use, Backup-Mode
- **Buffer storage for EV fast charging** – Increasing the usable output
- **Agricultural buildings** – Use of PV electricity after end of subsidy
- **Urban storage or new buildings** – Reducing the load on the transformer



- **Pramac Storage Systems** – Leading supplier of power electronics
- **Proven technology** – For a wide range of Battery applications
- **Strong team** – With a global partner
- **Reliable energy storage solutions** – Indoor / Outdoor / Container
- **Retrofitting of existing Pramac systems possible**



TECHNICAL DATA BATTERY INVERTER



TECHNICAL DATA		PBI 50K / 90K ON-Grid	PBI 90K-BU ON/OFF-Grid
Art. No.		422P050 / 422P090	423P090
Optional for installation*		Connection Box 50K / 90K (940P300.100)	Connection Box 90K (940P300.200)
DC Data			
DC operational range min. – max. (V)	620 – 1.000		
DC voltage range at nominal power (V)	650 – 900		
Nominal voltage DC (V)	720		
Max. operational current DC (A)	85 / 155		155
DC connection PowerUnit - ConnectionBox	1 Plus, 1 Minus: Connector with Button Activated Coupling		
AC Data – ON-Grid			
Apparent power (kVA)	50 / 90		90
AC Rated voltage AC, Uac (V)	400		
AC operational range min. – max. (V)	180 – 528		
AC grid connection / Grid types	3P, PE / TT, TN-C	3P, N, PE / TT, TN-C-S	
Nominal power factor / Range	1 / 0i ... 0c		
Rated frequency / Frequency Range (Hz)	50 / 45 ... 65		
Max. AC current, I _{max} (A)	73 / 130	130	
Max. THD (%)	< 3		
Max. efficiency (%)	98,4		
Initial short circuit current (Ik)	73 / 130	130	
AC Data – Backup Mode**			
Apparent power (kVA)	-	75	
AC Rated voltage AC, Uac (V)	-	400	
Max. peak current (A)	-	185	
Overload capability(%)	-	120	

** Only in combination with the Pramac Smart Transfer Switch (PSTS)

TECHNICAL DATA BATTERY INVERTER

	PBI 50K / 90K ON-Grid	PBI 90K-BU ON/OFF-Grid
Art. No.	422P050 / 422P090	423P090
Ambient Conditions		
Cooling	Smart active cooling	
Max. working temperature for nominal power (°C)	45	
Working temperature range (°C)	-25 to +60	
Rel. Air humidity (%)	0 – 100	
Max. elevation (m above sea level)	3.000	
Noise level (dBA)	< 70	
Environment classification (IEC 60721-3-4)	4K4H	
Type of protection	IP65	
Installation type	indoor / outdoor, vertical / flat	
Safety and Protection Functions		
Grid monitoring (acc. DIN VDE V 0126-1-1)	Voltage, Frequency, Passive and Active Anti-Islanding	
Grid separation	Gate Block / redundant Grid Relays	
Overvoltage category (IEC 60664-1)	DC: II / AC: III	
DC-precharge	integrated	
General Data		
Topology	Transformerless	
DC pole grounding	not allowed	
Interfaces	2 × Ethernet (Daisy-Chain), Bluetooth® BLE, 1 × Remote Off Signal	
Communication Protocols	Sunspec / MESA (Modbus TCP)	
Dimensions W × H × D (mm)	673 × 626 × 321	
Weight (kg)	69	73
Certificates		
EU Directive	2014/30/EU / 2014/35/EU / 2011/65/EU / 2015/863/EU	
Product safety	IEC 62109-1 / IEC 62109-2 / IEC 62477-1 / IEC 61439-1 / IEC 61439-2	
EMC	EN 61000-6-2 / EN 61000-6-4 / EN 61000-3-12 / EN 61000-3-11	
Environment	IEC 60068-2-2 / -2-78 / -2-6 / -2-27	
Grid Codes	DIN VDE V 0126-1-1 / VDE AR-N 4105:2018 / VDE AR-N 4110:2023 / TOR Stromerzeugungsanlagen Typ A/B / C10/11 / G99 / CEI 0-16, CEI 0-21 / NTS 631, UNE 217002 / EN 50549-1/-2 / AS 4777.2 / Eirgrid	

All certificates are available at www.pramac.com

Text and illustrations correspond to the technical status at the time of printing. We reserve the right to make technical changes. No liability for printing errors. The current version replaces all previous versions. You can find the latest version at www.pramac.com