



STAGE V
COMPLIANT

PMi SERIES

inverter generators





FREEDOM OF movement

Camping, tailgating, feel outdoorsy. Time to power up your leisure experience and enjoy your home away from home with all comforts: appliances and personal electronics at your fingertips with no battery-dependent worries.

Optimal solution to combine silent operation with less fuel consumption and tension stability. They guarantee maximum efficiency through the Economy Mode, that automatically adjusts the engine speed to the optimum level to provide excellent fuel economy and noise reduction. The PMi Inverter Series has a compact design and are equipped with a handle that allows you to carry the product easily.

The range is equipped with a 12 Volt battery charger + cables, useful for recharging your car battery.

- Stable power for safe operation of sensitive electronics
- Pramac OHV engine
- Low-oil level shutdown
- Economy mode for maximum fuel savings and noise reduction
- Ports for mobile electronics charging (USB and DC 12V)
- Digital display



INVERTER TECHNOLOGY: HOW DOES IT WORK?



The inverter technology improves the power quality. Inverter generators stabilize the output tension and provide high quality energy, which controls and stabilize the electrical supply. It is ideal for powering smart electronics, even computer and mobile phone.



PORTABILITY



DURABILITY



LOW NOISE



USB



RECOIL AND ELECTRIC START



DIRECT CURRENT



ATS CONNECTOR



REMOTE CONTROL



2 WIRE START

PMi 4500 EXCLUSIVE FEATURE

	PMi 1000	PMi 2500	PMi 3000	PMi 4500
Single Phase Max Power	950 Watts	2300 Watts	3000 Watts	4200 Watts
Single Phase Rated Power	850 Watts	2000 Watts	2800 Watts	3800 Watts
Voltage	230 V	230 V	230 V	230 V
Running time at 50% load	3.2 Hours	3.6 hours	6 Hours	9.7 Hours Eco mode
Tank Capacity	2.1 Litres	3.5 Litres	10 Litres	12 Litres
Fuel consumption 50% (l/h)	0.66 l/h	0.9 l/h	1.60 l/h	1.20 l/h
Fuel	Petrol	Petrol	Petrol	Petrol
Displacement	53 cc	120.8 cc	207 cc	224 cc
Speed (rpm)	Variable	Variable	Variable	Variable
Starting System	Recoil	Recoil	Recoil	Electric+Recoil
Guaranteed sound level (LWA)	89 LWA	93 LWA	96 LWA	93 LWA
Noise emission at 7 m	61 dB(A)	67.7 dB(A)	68 dB(A)	68 dB(A)
Dimensions LxWxH (mm)	480x250x395	535x305x460	555x400x450	578x422x500
Dry Weight	14 Kg	22.5 Kg	38 Kg	42.5 Kg
Socket type Standard EU	1 x Schuko 230V 16A 1 x DC 12V 6A n°2 USB 5V 2A	2 x Schuko 230V 16A 1 x DC 12V 6A n°2 USB 5V 2A	2 x Schuko 230V 16A 1 x DC 12V 6A	2 x Schuko 230V 16A 1 x DC 12V 6A
Socket type UK	1 x 230V 13A 3 Pin 1 x DC 12V 6A n°2 USB 5V 2A	2 x 230V 13A 3 Pin 1 x DC 12V 6A n°2 USB 5V 2A	2 x 230V 13A 3 Pin 1 x DC 12V 6A	
Battery charger	✓	✓	✓	✓
Economy Mode	✓	✓	✓	✓
Oil guard	✓	✓	✓	✓
Overload Protection	✓	✓	✓	✓
Hour meter		✓	✓	✓
Volt meter		✓	✓	✓
Frequency meter		✓	✓	✓
Fuel level gauge			✓	✓
Wheel kit			✓	✓
3xtra control			✓	✓



www.pramac.com | www.pramacparts.com

The product images shown are for illustration purposes only and may not be an exact representation of the product. The manufacturer reserves the right to introduce changes to models and features without prior notice. EN/04_2025_rev.2